



ABSORBED POWER

Ph. 07 33978677 or 1300 303 498

Email. paul@absorbedpower.com

Web. www.absorbedpower.com



Absorbed Power AGM GT12-150C

The C series range of AGM Batteries are designed specifically to have a large amount of stored current discharge between charging sessions. With a heavy non-porous battery plate, a different active chemical paste material and a stronger electrolyte than normal batteries, the C range of batteries produce superior performance for high power output and excellent deep cycle applications.

Battery Model	GT12-150C			
Designed Cycle Life	> 350 cycles @ -0.5CA to 9.6V			
Capacity (25°C)	20HR (7.7 A, 1.75V)	10HR (15A, 1.75V)	5HR (25.5A, 1.75V)	1HR (96A, 1.75V)
	154Ah	150Ah	127.5Ah	96Ah
Dimensions	Length	Width	Height	Total Height
	485mm (19.1inch)	172mm (6.77inch)	240mm (9.45inch)	240mm(9.45inch)
Approx. Weight	45Kg (99.2 lbs)			
Internal Resistance	Full charged at 25°C: 0.004 Ohm			
Self Discharge	3% of capacity declined per month at (25°C)			
Capacity Affected by Temp. (20HR)	40°C	25°C	0°C	-15°C
	102%	100%	85%	65%
Charge Voltage (25°C)	Cycle Use		Float Use	
	14.4-15V(-30mV/°C), max. Current: 37.5A		13.6-13.8(-20mV/ °C)	
CCA	1000			
Terminal Type	M6 Threaded Insert			

Applications

- Car Audio
- Cruiser / Yacht
- General Marine
- House Boat
- Caravan / Camper
- 4WD
- Radio / Comms Support
- House Batteries
- Truck
- Standby Power

24 month warranty
Refer to warranty
policy for terms and
conditions

